ED SMAER

Thesis subject 2014

Laboratory: Institut Jean le Rond d'Alembert (CNRS UMR 7190)

University: UPMC

Thesis supervisor: Guillaume Legros (section 62)

Contact: guillaume.legros@upmc.fr

Co supervisor: Didier Lucor (CNRS section 10)

Title of the thesis: Control of fire spread in spacecraft: role of ambient conditions

Collaboration within the thesis: Jean-Louis Consalvi - MdC IUSTI Marseille (France) Osamu Fujita - Pr Univ. Hokkaido (Japon)

Program affiliation:

PhD thesis funded at a level of 50% by Centre National d'Etudes Spatiales within the framework of the international project SAFFIRE (Spacecraft Fire Safety Demonstration)

This subject can be published on the doctoral school's website: Yes

Thesis's summary (Abstract)

For several decades, many sound scientific works on fire growth and the movement of smoke and heat have been providing the engineers with the information and tools that are necessary in the design of fire detection and the definition of the subsequent procedures. However, due to the specific conditions encountered in spacecraft, the usual tools for normal gravity fire detection design needs to be at least assessed into realistic space conditions and probably modified according to the discrepancies among detection thresholds in 1g and 0g, that could lead to unappropriate procedures, then disasters, following a misdetection -or a non-detection- in microgravity.

Along the Ph.D., the student will investigate flame spread over small flat samples in microgravity. The experiments will take place on board the Novespace zeroG airplane. The new experimental rig currently developed at UPMC will allow these experiments. The student will especially focus on setting detection systems that deliver relevant inputs to a fire spread control device. A specific attention will be paid to the control of the ambient atmosphere conditions (chemical composition, flow). These conditions are especially expected to deliver means of soot production control. Soot has been shown to play a key role into the radiative heat transfer which governs fire spread in the absence of buoyancy.

A numerical study will be performed in order to complete the experimental analysis. The student will use an existing numerical tool developed at the IUSTI UMR 7343 by Jean-Louis Consalvi and his co-workers. This code is well designed to model soot production and radiative heat transfer in microgravity laminar diffusion flames. It solves the elliptic governing equations in a low Mach formulation by using the finite volume method, considers detailed gas-phase chemistry and complex thermal and transport properties, and the soot production is computed by an advanced PAH-based soot model. Radiative heat transfer is calculated by using the Finite Volume Method coupled with the Full-Spectrum Correlated-k method to determine the radiative properties of the participating species. A reduced model including the radiative heat transfer and soot production will be considered to achieve "real-time" computations. This approach will rely on assumptions, therefore limitations that induce a level of uncertainties. These need to be decently quantified.

This Ph.D. is expected to contribute to the international project "Spacecraft Fire Safety Demonstration" lead by NASA in close collaboration with European, Japanese, and Russian partners. Within the framework of this project, fires will spread over samples of real length scale (~1m) within real time scale (~20 minutes) into three actual spacecraft, i.e. Cygnus supply vehicles. These extraordinary experiments are a worldwild première to date into the challenging Mission To Mars.

_

¹ members of the international group: http://www.spacefiresafety.byg.dtu.dk/People.aspx